

## **ACCESS CONTROL**

## SDC200 SINGLE DOOR CONTROLLER



**FEATURES** 

- Supports various lock types, including solenoid, magnetic and motorized
- Sensor inputs for request-to-exit and monitoring of door status
- Compatible with Habtech's PRC200 Proximity Reader Controller, WRC200 Wiegand Reader Controller, TRC200 Touch Reader Controller and KPC200 Keypad Controller
- ▼ Accepts standard Echelon Twisted-Pair Control Modules
- Simple connection and easy mounting on standard DIN rails
- Ideal for physical access control applications


LONWORKS, LON and Neuron are trademarks of Echelon Corporation registered in the United States and other

The Smart Touch is a registered trademark of Habtech Communications Inc.

The SDC200 Single Door Controller incorporates application firmware and a LONWORKS® control module. As a member of The Smart Touch® Product Family, SDC200 is fully compatible with Habtech ST2000 Security Management Systems.

These controllers are designed for LONWORKS control system applications where door control, access control and/or door monitoring are required, such as office buildings, correctional institutions etc.

The SDC200 controller contains a relay output and digital inputs for interface to electric locks, door position switches and request-to-exit devices.



## TECHNICAL SPECIFICATIONS

**Network Interface** TP/FT-10 Free Topology at 78 Kbps

(Contact factory for other transceiver options)

Input Power 9-15 Vdc at typical current of 100 mA

Operating 0 to 50°c ambient temperature Environmental 25 to 95% relative humidity

-40 to 85°c ambient temperature

Storage 0 to 95% relative humidity

**Physical Dimensions** Packaged 74mm (H) 25mm(W) 102mm (L)

Connectors Phoenix MSTB 2,5 series, 8 position (2)

1A/30V DC; 0.25A/120V AC Relay

\* Specifications subject to change without notice.



ST2000 Pro ... CONTROLS ALL