

## ACCESS CONTROL


## SDC210 SWING DOOR/WATCHTOUR CONTROLLER




The SDC210 Swing Door/Watchtour Controller incorporates application firmware and a LONWORKS® control module. As a member of The Smart Touch® Product Family, SDC210 is fully compatible with Habtech ST2000 Security Management Systems.

These controllers are designed for LONWORKS control system applications where door control and/or watchtour monitoring are required, such as detention centres and correctional institutions.

The SDC210 controller contains relay outputs and opto-isolated digital inputs for interface to electric locks, door position switches, request-to-exit devices and watch tour stations. All inputs and outputs are over-current protected with .5A polyswitches (self resettable fuses).





## **FEATURES**

- Supports various lock types, including solenoid, magnetic and motorized
- ▼ Sensor inputs for monitoring of door status and watchtour activity
- ▼ Compatible with Habtech TSS100 Touch Switch Station
- ▼ Accepts standard Echelon Twisted-Pair Control Modules
- ▼ Simple connection and easy mounting on standard DIN rails
- Ideal for physical access control applications in correctional institutions

LONWORKS, LON and Neuron are trademarks of Echelon Corporation registered in the United States and other countries.

The Smart Touch is a registered trademark of Habtech Communications Inc.

## TECHNICAL SPECIFICATIONS

Network Interface TP/FT-10 Free Topology at 78 Kbps

(Contact factory for other transceiver options)

Input Power 9-15 Vdc at typical current of 100 mA

Environmental Operating 0 to 50°c ambient temperature

25 to 95% relative humidity

Storage -40 to 85°c ambient temperature

0 to 95% relative humidity

Physical Dimensions Packaged 74mm (H) 25mm(W) 102mm (L)

Connectors Phoenix MSTB 2,5 series, 8 position (2)

\* Specifications subject to change without notice.

